

# Product Information Sheet

## COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

<b>Supplier's name or trade mark:</b> EIZO			
<b>Supplier's address:</b> EIZO Europe GmbH, Belgrader Straße 2, 41069 Mönchengladbach, Germany			
<b>Model identifier:</b> RadiLight			
<b>Type of light source:</b>			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	NMLS	Connected light source(CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
<b>Product parameters</b>			
Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on mode (kWh/1000h), rounded up to the nearest integer	3	Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	130 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set	6500
On-mode power ( $P_{on}$ ), expressed in W	2.5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	-
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set	85
Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)	Height	186	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	184	
	Depth	16	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0.313 0.329
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	26	Survival factor	1.00
the lumen maintenance factor	0.93		

(a)<sup>-1</sup> : not applicable;

(b)<sup>-1</sup> : not applicable;

